



Rapid Spill Control Pty Ltd
 PO Box 7195
 Wetherill Park
 NSW 2164
www.rapidspillcontrol.com.au

Drain Seal and Flexible Spill Barrier Chemical Suitability Guide

The Drain Seal & Flexible Spill Barrier is suitable for use with the following chemicals and substances:

Acids	Petroleum Solvents	Caustics	Alcohols and Glycols	Miscellaneous
Acetic (to 60%)				Cutting Oils
Chromic				Formaldehyde
Citric			Butyl Alcohol	Animal Oils
Hydrochloric	Gasoline		Ethyl Alcohol	Vegetable Oils
Hydrofluoric	Kerosene	Ammonium Hydroxide	Methyl Alcohol	Hydraulic Fluid
Muriatic (to 38%)	Mineral Spirits	Potassium Hydroxide	Denatured Alcohol	Printing Inks
Nitric (to 70%)	Naptha	Sodium Hydroxide	Isopropyl Alcohol	Aliphatic
Phosphoric			Ethylene Glycol	Solvents
Sulfuric (to 50%)			Propylene Glycol	Methyl Ether
Tannic				Acetate

The following spills will be controlled, however extended exposure may degrade Flexible Spill Barrier or Drain Seal:

- Acetone
- Phenols
- Ethyl Acetate
- Trichloroethylene
- Benzene
- Aromatic Petroleum Distillates

